

光学特性データ

測定サンプル | リフレクションズアクティブ170 3D

STD. WHITE =	11.505
PG(H) =	1.70
α (H)R =	53.00
α (H)L =	53.00
β (H)R =	85.00
β (H)L =	85.00

(α) = 半値角 (ピークゲインの1/2の値)
 (β) = 1/3値角 (ピークゲインの1/3の値)

HORIZONTAL		
角度	nt	Gs
-80.0°	8.054	0.70
-75.0°	8.693	0.76
-70.0°	9.14	0.79
-65.0°	9.396	0.82
-60.0°	9.652	0.84
-55.0°	9.679	0.84
-50.0°	9.907	0.86
-45.0°	10.035	0.87
-40.0°	10.163	0.88
-35.0°	10.291	0.89
-30.0°	10.547	0.92
-25.0°	10.866	0.94
-20.0°	11.377	0.99
-15.0°	12.144	1.06
-10.0°	13.742	1.19
-5.0°	16.427	1.43
-2.5°	19.551	1.70
+2.5°	19.49	1.69
+5.0°	16.235	1.41
+10.0°	13.615	1.18
+15.0°	12.017	1.04
+20.0°	11.25	0.98
+25.0°	10.738	0.93
+30.0°	10.483	0.91
+35.0°	10.285	0.89
+40.0°	10.159	0.88
+45.0°	10.02	0.87
+50.0°	9.9	0.86
+55.0°	9.669	0.84
+60.0°	9.642	0.84
+65.0°	9.386	0.82
+70.0°	9.076	0.79
+75.0°	8.629	0.75
+80.0°	7.99	0.69

